

N26064RF01




N26064SF01



DETAILS




ANTI-GLARE Low UGR <9




LIGHT DISTRIBUTION

10W 3000K 15°



D(cm)	h(m)	E(lx)
35.42	1	5206
70.85	2	1302
106.27	3	578.5
141.7	4	325.4
177.12	5	208.2

15W 3000K 24°



D(cm)	h(m)	E(lx)
46.35	1	5391
92.7	2	1348
139.04	3	599
185.39	4	337
231.74	5	215.7

DEEP ANTI GLARE Series

Recessed Downlight (Low UGR<9),
10W - 15W / 20W - 25W / 30W - 35W

GENERAL

IP20 Indoor lighting type
IP44 Option
recessed / fixed / round / square

SPECIFICATION

Material : Die-cast aluminum body.
Frame Color : Black
Trim Color : White, Black, Silver
Optical : cut-off 48° (UGR<9)

LED LAMPS

Module COB M60, M70, M90
CRI : 90+
Color Consistency : SDCM ≤3
CCT : 2700K, 3000K, 3500, 4000K
Tunable White : 2700K - 6000K
Dim to Warm : 2000K-3000K
Beam angle : 15°, 24°, 38°, 50°
Average lifetime : 50,000h@80% (L80)
Warranty : 5 years limited warranty

SECONDARY REFLECTOR COLOR

☐ Black
☐ Bright Silver
☐ Matte Silver

ANTI-GLARE ACCESSORY

☐ Honeycomb filter ☐ Soft lens

ELECTRICAL (driver)

Input voltage : 220-240V, 50/60Hz
Power factor : >0.9

DIMMING CONTROL

☐ N = On-off ☐ T = TRIAC
☐ V = 0/1-10V ☐ D = DALI
☐ X = 0-10V/Triac ☐ C = CASAMBI

INSTALLATION




Recessed mounted.

DRAWING (mm) :

N26064RF01 / N26064SF01

N27074RF01 / N27074SF01

N29094RF01 / N29094SF01



ORDER INFORMATION

CODE No.	LED POWER (WATT/ LUMEN)	TRIM COLOR	CRI (Ra)	CCT (K)	BEAM (D)
☐ N26064RF01	☐ 10W 878-988lm	☐ W White	☐ 90+ SDCM ≤3	☐ 2700K ☐ 3000K ☐ 3500K ☐ 4000K	☐ 15°
☐ N26064SF01	☐ 15W 1105-1320lm	☐ B Black			☐ 24° ☐ 38°
☐ N27074RF01	☐ 20W 1580-1890lm	☐ S Silver		☐ TW Tunable White 2700K-6000K	☐ 50°
☐ N27074SF01	☐ 25W 1075-2240lm			☐ DW Dim to Warm 2000K-3000K	
☐ N29094RF01	☐ 30W 2220-2683lm				
☐ N29094SF01	☐ 35W 2730-3040lm				

