


PROJECT : _____
 LOCATION : _____
 TYPE OF LUMINAIRE : _____
 PRODUCT DATASHEET



Code No. N2101

Deep Recessed Downlight, 1xMR16

type : recessed / adjustable / round

GENERAL

IP20, IP44 Indoor lighting type
 Deep anti glare low UGR
 Replace the MR16 bulbs front side

SPECIFICATION

Material : Die-cast aluminum body.
 Finishing Color : Matte White
 Reflector : Matte Black
 Adjustable : 0°-25° tilt

LIGHT SOURCE

LED MR16 GU5.3 12V
 CRI : 97 (R9>85)
 Color Consistency : SDCM ≤3
 Lumen : 450-500lm.
 CCT : 2700K, 3000K, 4000K
 Beam angle : 10°, 24°, 36°, 60°
 Average lifetime : 40,000h
 Optical : Direct illumination

ELECTRICAL (driver)


Input voltage : 220-240V, 50/60Hz
 Power factor : >0.9
 Insulation Class : II
 Dimming - Options
 Standard : EN IEC 55015:2019



INSTALLATION

Recessed mounted.

DRAWING (mm) :



ACCESSORY

Glass cover, IP44



ORDER INFORMATION

CODE No.	POWER (W)	LED (Lamp)	CRI (Ra)	CCT (K)	BEAM (BA°)	TRIM COLOR	DIMMING (Options)
N2101	1x6.7W	PHILIPS	97	<input type="checkbox"/> 2700K	<input type="checkbox"/> 10°	<input type="checkbox"/> White	<input type="checkbox"/> On-off
N2101	1x6.5W	PHILIPS	90	<input type="checkbox"/> 3000K <input type="checkbox"/> 4000K	<input type="checkbox"/> 24° <input type="checkbox"/> 36° <input type="checkbox"/> 60°	<input type="checkbox"/> Black	<input type="checkbox"/> Triac

