


PROJECT : _____
 LOCATION : _____
 TYPE OF LUMINAIRE : _____
 PRODUCT DATASHEET



Model : NIP-201

Deep Recessed Downlight, 1xGU5.3
 type : recessed / adjustable / round

GENERAL

IP20, IP44 Indoor lighting type
 Deep anti glare low UGR
 Replace the MR16 bulbs front side


SPECIFICATION

Material : Die-cast aluminum body.
 Finishing : Polyester Powder Coated
 Trim Color : Matte White
 Reflector : Matte Black
 Adjustable : 0°-25° tilt

INSTALLATION

Recessed mounted.

DRAWING (mm) :



AREAS APPLICATIONS

Hospitality, Hotels, Retail, Restaurants,
 Offices, Public & Commercial Building
 Supermarkets, Museums, Galleries.

LIGHT SOURCE

LED MR16 GU5.3 12V
 CRI : 90 / 97 (R9>85)
 Color Consistency : SDCM ≤3
 Lumen : 450-500lm.
 CCT : 2700K, 3000K, 4000K
 Beam angle : 10°, 24°, 36°, 60°
 Optical : Direct illumination
 Average lifetime : 40,000h

ELECTRICAL (driver)

Input voltage : 220-240V, 50/60Hz
 Power factor : >0.9
 Insulation Class : II
 Dimming - Options
 Standard : TIS 1955-2551

ACCESSORY

☐ Glass cover, IP44



ORDER INFORMATION

CODE No.	POWER (W)	LED (Lamp)	CRI (Ra)	CCT (K)	BEAM (BA°)	TRIM COLOR	DIMMING (Options)
NIP-201	1x6.5W	PHILIPS	90	☐ 2700K	☐ 10°	☐ White	☐ On-off ☐ Triac
	540lm	MASTER		☐ 3000K	☐ 24°		
	1x6.7W	PHILIPS	97	☐ 4000K	☐ 36°		
	480lm	ExpertColor			☐ 60°		
NIP-201G	1x6.5W	PHILIPS	90				
	540lm	MASTER					
	1x6.7W	PHILIPS	97				
	480lm	ExpertColor					

Application

Application

